

Portable Digital Gas Flow Meter

# GF 1010

**Handy and Compact**

**Wide Flow Range**

**Easy to Operate**



The new pocket sized GF 1010 gas flow meter makes gas flow measurement easier and more accurate, helping to eliminate user errors. The GF 1010 is an essential tool for troubleshooting and routine maintenance of your gas chromatograph. The LCD display with back light makes reading flows clear and easy. As an option, there is a Silicone protection cover available to protect the flowmeter.

## Specifications

Flow Range:	0.5 - 1200 ml/min No need to select a gas type due to volume flow meter technique. Mixed gas can also be measured.
Accuracy:	±3% or ±0.3 mL/min whichever is greater (for calibration gas N2)
Operating temp. range:	10 - 40°C (Accuracy Range 15 - 30°C)
Silicone tube:	I.D. = 3mm, O.D. = 7mm (maximum temperature = 200°C)
Measurable gases:	N2, Air, He, Ar, H2, etc. (no corrosive and humidity gas)
Battery:	2 AA Batteries
Display:	LCD with back light
Standards:	WEEE, RoHS, CE
Dimensions:	76mm(W)×135mm(D)×35mm(H)
Weight:	approx. 240 gram without battery
Functions:	Zero Adjustment, Battery indicator, selectable auto power off

## Options and Part Numbers

2709-10100, Gas Flow Meter GF 1010 (includes battery, tube and manual)

Options:


2709-10102, GF 1010 replacement Silicone Tube

2709-10110, Silicone Cover (Navy Blue)

2709-10103, TCD Vent Adaptor (1/8" Swagelok Adaptor)

2709-55015, Capillary Column Adaptor

2709-10101, Calibration of GF 1010 with certificate (not included with new unit)



Capillary Column Adaptor option



GF 1010 with Silicone Cover

## Contact

GL Sciences B.V. | De Sleutel 9 | 5652AS Eindhoven | The Netherlands | [info@glsciences.eu](mailto:info@glsciences.eu) | [www.glsciences.eu](http://www.glsciences.eu)